



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b>  <b>H04L 29/06</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 99/56445</b>  <b>(43) International Publication Date:</b> 4 November 1999 (04.11.99)
<b>(21) International Application Number:</b> PCT/SE99/00621  <b>(22) International Filing Date:</b> 19 April 1999 (19.04.99)  <b>(30) Priority Data:</b> 9801524-1      28 April 1998 (28.04.98)      SE 9802666-9      4 August 1998 (04.08.98)      SE  <b>(71) Applicant (for all designated States except US):</b> TELIA AB (publ) [SE/SE]; Mårbackagatan 11, S-123 86 Farsta (SE).  <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> HUBBARD, Elisabeth [SE/SE]; Operettvägen 28, S-142 43 Skogås (SE).  <b>(74) Agent:</b> PRAGSTEN, Rolf; Telia Research AB, Vitsandsgatan 9, S-123 86 Farsta (SE).		<b>(81) Designated States:</b> EE, LT, LV, NO, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>Without international search report and to be republished          upon receipt of that report.</i>
<b>(54) Title:</b> A (GSM-GPRS) NETWORK WITH INTERNET PROTOCOL COMBINED FUNCTIONALITY  <div style="text-align: center;"> <pre> graph TD     AUC --- HLR     HLR --- EIR     HLR --- SMS_gateway[SMS-gateway]     HLR --- MSC_MLR[MSC/MLR]     HLR --- G_MSC[G-MSC]     SMS_gateway --- SM_SC[SM-SC]     EIR -.-&gt; MAP-F  MSC_MLR     MSC_MLR -.-&gt; MAP-D  HLR     MSC_MLR -.-&gt; MAP-H  G_MSC     G_MSC -.-&gt; MAP-C  HLR     G_MSC -.-&gt; MAP-C  MSC_MLR     MSC_MLR --- BSS     subgraph BSS         BTS         BSC     end     BSS --- Abis  MSC_MLR     MSC_MLR --- ISUP  G_MSC     G_MSC --- PSTN       </pre> </div>		
<b>(57) Abstract</b>  A network (GSM/GPRS) with functionality which is related to distribution of keys for authorisation, authentication and ciphering, subscriber information handling and CDR generation. The functionality is combined with the Internet protocol for transporting data and handling macro mobility to form an efficient as well as secure core network for mobile users.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## A (GSM-GPRS) NETWORK WITH INTERNET PROTOCOL COMBINED FUNCTIONALITY

The present invention relates to a network (GSM/GPRS) with functionality which is related to distribution or keys for  
5 authorisation, authentication and ciphering, subscriber information handling and CDR generation.

Since GSM (Global System for Mobile communication) was introduced in the Nordic countries in 1992, penetration has reached as high as 40 % - and is still increasing rapidly.  
10 However, this also means that large investments have been made in this system during those years. GSM is primarily a system for speech communication, which makes up 98 % of the total traffic. Data services exist, but are slow, inefficient and expensive since they are run on circuit  
15 switched connections.

In the year 2000, GSM will be enhanced with a general packet data service (GPRS), which uses the same radio access as GSM together with a new core network, based on IP. A maximum of about 150 kbps can be delivered, but the actual  
20 bandwidth will be significantly lower due to the presence of other users and the quality of the radio connection. Databases and servers containing subscriber data, equipment data, short message handling, etc. already in operation for the GSM system will be reused for GPRS.

25 Two years later, in 2002, UMTS (Universal Mobile Telecommunication System) will be taken into operation, delivering up to 2 Mbit/s over radio with full mobility. Contrary to GPRS, the UMTS radio access network will be built from scratch and existing core networks will be  
30 modified and reused to a large extent. For the initial phase of UMTS, the GPRS and GSM core networks are the most

interesting candidates because of their capabilities to handle mobile terminal and users.

UMTS will support mixed services, which means everything from Internet access to multimedia conferencing. Judging  
5 from how fixed Internet access presently is booming, one is tempted to believe that mobile Internet access will become equally popular. In addition, taking into account the development of IP telephony during the last year and the fact that video standards like H.323 [H.323] are being  
10 developed for IP networks, it is quite possible that an IP based network is the most future proof solution for UMTS. When constructing public mobile networks, one has to keep in mind that radio resources are scarce and that these networks are expensive to operate, and hence, it is necessary for the  
15 operator to have the means to charge the users for services that they use. In the near future, it is doubtful that this requirement can be fulfilled by (Mobile)IP networks. Operators, who have large investments in GSM and GPRS systems, could, however, reuse parts of those to complement  
20 the shortcomings of IP networks.

GSM and its future packet data service, GPRS, has an advanced system for

- authorisation and authentication of users/terminals,  
25 including key distribution
- ciphering over radio, including key distribution
- subscriber information handling
- CDR generation

through the VLR functionality in the MSC and the SGSN  
30 respectively and through the HLR and as well as other data bases.

The GPRS backbone is, however, not optimal because of its many successive protocol layers, which results in long delays and large overhead.

5 The Internet Protocol is simple, flexible and optimized for transporting data through networks. Enhanced with MobileIP for handling mobility, it could be used as a core network for mobile systems, i.e. the mobile user could get direct access to the Internet without passing through an additional  
10 network, like GPRS backbone. However, IP lacks support for subscriber handling and charging. Authentication and encryption is supported to ensure integrity and confidentiality but the key distribution, which is not standardized, is still a problem. The invention offers a  
15 solution of the security problem and form an efficient as well as secure core network for mobile users.

The solution to the problem is described in the claims.

20 UMTS is presently being standardardized and its core network will, in an initial phase, be based on the GPRS core network.

Advantages to the invention is that is possibly to use the fixed network in a more efficient way, when the GPRS  
25 backbone, in a later stage, is replaced by a purer IP network for transporting user data under the condition that the security issues are solved.

30 Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 The basic GSM architecture.

Figure 2 Overview of the GPRS logical structure

5 Figure 3 The GPRS Protocol architecture. The GPRS backbone is shaded

Figure 4. General UMTS Architecture with the reference points currently identified in UMTS, March1998  
10 [UMTS23.01].

Figure 5. Using IP for service transport end-to-end.

Figure 6. Scenario with Mobile IP support for intra  
15 UTRAN mobility and modified SGSN's to handle subscriber data etc.

Figure 7. Scenario with Mobile IP supporting roaming in  
20 foreign networks.

Figure 8. Evolution scenario for UMTS. The IWU-Gb and IWU-Gbu are taken from [umts23.20].

25 A glossary of the abbreviations used in this patent specification is set out below to facilitate an understanding of the present invention.

30	AN	Access Network
	AUC	Authentication Center
	BSS	Base Sub System
	CN	Core Network
	DHCP	Dynamic Host Control Protocol

	ETSI	European Telecommunication Standardisation Institute
	GGSN	Gateway GPRS Support Node
	GPRS	General Packet Radio Service
5	GTP	GPRS Tunneling Protocol
	GSM	Global System for Mobile communication
	HA	Home Agent
	HLR	Home Location Register
10	SP	Service Provider
	IP	Internet Protocol
	IWU	InterWorking Unit
	MS	Mobile Station
	MSC	Mobile Services Switching Center
15	MT	Mobile Termination
	PLMN	Public Land Mobile Network
	PSTN	Public Switched Telephone Network
	QoS	Quality of Service
	SGSN	Service GPRS Support Node
20	SIM	Subscriber Identity Module
	SP	Service Provider
	TCP	Transport Control Protocol
	UDP	User Datagram Protocol
	UE	User Equipment
25	UMTS	Universal Mobile Telecommunications System
	UTRAN	UMTS Terrestrial Radio Access Network
	VLR	Visitor Location Register
30	UMTS, the third generation cellular system currently being specified by ETSI, is the first cellular system to be optimized for extensive use of data services mixed with speech. One solution is to use the IP protocol for the	

transport of services across core and access networks. Using a MobileIP core network would allow roaming between the radio access networks in a rather straightforward way. However, radio resources are scarce and public cellular systems are expensive to operate, and hence, it is of great importance that the users can be properly charged for services that they use. In the near future, it is doubtful that this requirement can be fulfilled by (Mobile)IP networks. Instead, parts of GSM/GPRS could be reused to complement the functionality of IP networks.

In this description, a network scenario is presented where the UMTS core network is based on Mobile IPv6, which supports roaming and possibly also handover between UTRAN's. Since the GSM/GPRS system already has several key functions to handle mobile users, e.g. subscriber data, access control, keys for encryption over radio, accounting information, the GPRS SGSN node should be reused to handle the setup of lower layer communication, including authentication and check of subscriber profile etc. A successful lower layer setup should be required in order to obtain a MobileIP care-of address. The mechanisms for distributing authorization and encryption keys in GSM/GPRS can also be utilized for distributing keys for the IPsec protocol.

Examples, describing how MobileIP and part of the GPRS core network could operate with a UMTS radio access network are presented later on in the description. The following three sections will give a brief introduction to those parts of GSM, GPRS, UMTS and IP that are relevant for this study. These are followed by a short discussion on using IP end-to-end in mobile networks, before presenting the examples.



GSM

GSM is a digital cellular system, primarily designed and used for speech communication[gsm]. A few data services and a rich set of supplementary services are standardized. The  
5 GSM network is built up of BSS's (Base Sub System), MSC/VLR's (Mobile Services Switching Center/Visitor Location Register), HLR's and a few other data bases and service nodes as illustrated in figure 1. The BSS contains base stations and base station controllers. Each terminal is  
10 equipped with a subscriber identity modules (SIM), which is a smart card containing, among other things, the user identity.

The MSC is the heart of the GSM system. It's duty is to:

- perform switching
- 15 • detect new mobile terminals in its service area and perform authentication and authorization procedures with these terminals
- collect information about users from their HLR and store the information in the VLR
- 20 • register location updates and store them in the VLR
- assist when handover takes place between MSC's
- create records for charging

Frequently, the VLR is integrated in the MSC. The Gateway-  
25 MSC is an MSC with additional functionality to handle traffic to and from the fixed network. For incoming traffic the G-MSC asks the HLR for routing information to the current MSC of the user.

The MSC communicates with databases like the home location  
30 register (HLR) and the equipment identity register (EIR) via

an SS7 based signaling system called MAP (Mobile Application Part).

The HLR stores the identity and user data of all the subscribers belonging to the area of the related G-MSC. The  
5 IMSI (International Mobile Subscriber Number), the phone number, service profile etc. are permanently stored in the HLR. For routing of incoming traffic, the user's current VLR and forwarding information is stored temporarily.  
Authentication and ciphering keys, which are derived in the  
10 AUC (AUthentication Center) are also available from the HLR.

Authentication and authorization of the terminal takes place each time a connection is setup, i.e. for each call. The authentication procedure is based on the authentication algorithm, which is stored on the SIM card and in the AUC.  
15 The AUC picks a random number from which the algorithm creates the authentication key. The random number and the key are then passed on to the HLR and the VLR, which sends the random number to the mobile terminal. The SIM card uses the random number to produce the key, which is returned to  
20 the network via the terminal. A comparison of the key received from the terminal and the one originating from the AUC will tell if the terminal is the expected one. The same method is used for giving the terminal the encryption key, but a different algorithm is used. This has the advantage  
25 that the encryption key is never sent over radio where it could easily be picked up by anyone. These algorithms are known nowhere outside the home network. On the terminal side, the algorithms are embedded in the SIM card and are available neither to the terminal nor to the user.

GPRS

GPRS (General Packet Radio Service) [GSM 03.60] is a packet switched service which, to a large extent, is based on a combination of GSM infrastructure, IP technology and a set of new functionality. Figure 2 describes the overview of the GPRS logical architecture. The main advantage of GPRS is that the limited radio resource is used only when there is data to transmit. There are two kinds of support nodes in the backbone, SGSN's (Service GPRS Support Node) and GGSN's (Gateway GPRS Support Node).

The main functions of the SGSN are to:

- perform authentication and other procedures to let new terminals connect to its service area
- send/receive data packets to/from the GPRS mobile
- keep record of the mobile's location inside its service area
- route data packets from one GPRS operator to another
- produce charging data records for the charging and billing system

The SGSN communicates with the HLR, the EIR, the SMS center etc. via a GPRS version of MAP.

The main functions of the GGSN are to:

- route data packets from one GPRS operator to another
- route mobile terminated data packets to appropriate SGSN where the mobile is currently located
- act as a gateway between GPRS network and external data networks (IP, X.25, etc.)

- handle de/encapsulation of user data protocol packets when communicating with external data networks.
- produce charging data records for the charging and billing system

GPRS Tunneling Protocol, GTP[gprs09.60], which is a specific to GPRS, tunnels user data packets between SGSN's and GGSN's. This enables the network to support transmission of several packet data protocols, even if the protocol is not supported by all SGSN's. GTP also transports signaling data for mobility handling between the nodes. As illustrated in figure 3, GTP is placed on top of the transport IP and UDP layer in the protocol stack. By using a non-standard protocol to transport user data, it is probably more difficult for users to do anything harmful to the system. On the other hand, it makes it impossible to use standard IP tunneling mechanisms without special solutions for GTP. An example is future resource reservation protocols, which are likely to operate in combination with standard IP-in-IP tunneling.

### UMTS

The UMTS system, which currently is under specification in ETSI, is based on a new UMTS Terrestrial Radio Access Network (UTRAN) and existing, but evolved, core networks (CN) such as IP, GSM/GPRS CN or ATM [umts23.01]. The interworking units (IWU) adapt the different CN's to the Iu interface if needed. The GRAN and the CN's may evolve independently of each other, while the IWU's follow the evolution of CN's and AN's to insure interconnection between these parts. For flexibility, the user equipment consists of

different modules of which one is a UMTS version of the GSM SIM card, the USIM. A general view of the logical modules and reference points is shown in figure 4.

- 5     The UTRAN will probably have an internal mobility management system, which means that, for routing, the CN only needs to keep track of in which UTRAN the mobile terminal is located. The CN will have to handle the subscriber information management, basic call handling,  
10    paging initiation, service feature analysis, security issues, charging, etc. Evolved versions of the GSM and GPRS CN's are foreseen for the initial phase of UMTS [umts23.20].

Primarily, the IWU will deal with translation of protocol messages and network parameters, in those cases where the  
15    protocols in the CN and in the UTRAN are different. If the CN does not support functionality required for a UMTS CN, the IWU could contain intelligence to enhance the CN. The choice of protocols over the Iu interface has not yet been made.

## 20    The Internet Protocol

The Internet Protocol, IP, is designed to route IP packets across networks and network boundaries in a flexible and efficient way. Because of its popularity, many services have been developed to run on top of the IP protocol. Today, it  
25    is not unusual to implement virtual IP networks within other networks based on e.g. ATM or IP, which creates extra security, but also additional overhead and processing time. The GPRS backbone is one example of such a network. Taking into account that UMTS will not be introduced until year  
30    2002, we only consider IPv6 [ipv6] here.

MobileIPv6 [mobip] is designed to deal with "macro" mobility management, i.e. the movements of mobile nodes

between different IP subnets. Routing in the Internet is based on fixed IP addresses, which depends on the subnet, through which the terminal is connected to the Internet. When connected to a foreign network, the mobile node needs a  
5 temporary address using the prefix of the visited network, a care-of address, to be able to receive packets.

Briefly, MobileIPv6 works in the following way:

- 10 • When the mobile node arrives in a foreign subnet, it acquires a care-of address using the IPv6 address autoconfiguration.
- 15 • The mobile node registers its care-of address with a router in its home subnet which acts as the node's Home Agent (HA). The home agent uses proxy Neighbor Discovery to intercept the IPv6 packets addressed to the mobile node's home address. The packets are then tunneled to the mobile node's care-of address using IPv6 encapsulation. This means that the mobile node can always be addressed by its home address, independently of which subnet it is roaming in.
- 20 • When packets, which are tunneled from the home agent, arrive at the mobile node immediately sends a message, which includes its current care-of address, to the communicating node. After receiving such a packet, the communicating node will send packets directly to the  
25 care-of address. This way, MobileIPv6 inherently supports optimized routing, which minimizes the load on the home subnet. When changing care-of address, the mobile node sends its new care-of address to its home agent and all other nodes that it is communicating with.

30

### Using IP for Service Transport Across Different Networks

Traditionally, telecom systems have been developed with one kind of transmission, for one or a few specific and well  
5 specified services which need support by the network. GSM is one example of these kind of systems where the time-to-market for new services is too long to be competitive.

UMTS should support mixed services, services provided by third-party, etc and new services must be easy and fast to  
10 implement. One possible solution is to use IP as a common format to deliver services end-to-end. This does not necessarily mean that the IP routing mechanisms have to be utilized in all the different networks. For example, the UTRAN has to manage micro mobility, which includes frequent  
15 and fast movements between base stations, which Mobile IP is not designed to handle. Instead, the IP layer could be provided a point-to-point connection between the IWU and the mobile terminal while the UTRAN handles the changing connections underneath.

20 The main advantages of this approach is that already today, an abundance of services and information is available on the Internet. Having direct Internet access from the mobile terminal would facilitate the convergence of fixed and mobile networks on a service level.

25 In figure 5, the end-to-end IP layer is mapped onto the UMTS architecture. The IWU would provide interworking between the lower layers of the core network and the access network.

GSM, IP and Broadband Radio Access - a Mix that  
Matches

As we have seen in previous sections, the UMTS UTRAN together with GSM/GPRS core networks would give us a system, which would handle mobile users excellently and provide high bandwidth connections over the radio interface. There is also support for the operator to profit from running such a network. However, neither GSM nor GPRS are designed for large volumes and the GPRS backbone is rather inefficient due to the large overhead.

On the other hand, IP is simple and flexible for transporting data through networks. Enhanced with MobileIP, which is optimized for roaming between subnets, it is an interesting UMTS core network candidate. Unfortunately, it's support for subscriber handling and charging is poor.

Let us therefore study how the different parts from IP, GPRS and UMTS could interwork to support mobility. First, we will study the case, which is illustrated in figure 6, where the terminal stays within its home IP network :

- The mobile terminal arrives at a new UTRAN and listens to the radio broadcast messages, which contain information about radio parameters, network and cell identity, etc. as well as information about available core networks, service providers, service capabilities etc.
- The mobile terminal sends a registration request including parameters such as identity, desired service provider etc.
- The UTRAN forwards the registration request to the SGSN, which processes it:



- The SGSN contacts the HLR of the mobile terminal to collect data to perform an authentication procedure.
- Once the terminal is authenticated and found to be allowed in the present UTRAN, all information over the radio interface can be encrypted. Encryption keys are obtained from the HLR. A random number is sent to the mobile which can calculate the key with an algorithm stored in the terminal. This way, the key is not sent over the radio interface.
- At this point, the terminal also gets registered in the UTRAN along with location data and radio specific information.
- Now, the terminal can start communicating over the IP layer. The terminal listens to router advertisement messages and solicit the nearest DHCP server [dhcp] to obtain a configuration parameters and a care-of-address. It is assumed that only stateful address configuration will be used, since it gives a better support for registration of the terminals than stateless. Logically, we include the IP functionality in the SGSN and call the entire unit SGSN' and the HLR records include the care-of address of the mobile terminal.
- The mobile terminal will then contact its home agent to register its new care-of address according to standard MobileIP.
- The home agent has to accept or reject the registration of a care-of address. Before making a decision, the home agent could contact the HLR (via a new interface) to obtain information that this terminal is properly registered. In addition, the keys needed for using the

IPsec authentication header and/or the encapsulation security payload [ipsec] could be obtained from the HLR. The mobile terminal can derive its keys from information on its USIM in the same way as in the GSM system.

- While the terminal is connected and transmits data, charging data records are produced by the SGSN'. Systems for billing and customer handling, already in operation for GSM, can easily be used also for UMTS.

10

In figure 7, the mobile terminal is roaming in a foreign network. The procedure for registering in that network is very similar to the home network case, the only difference being that the visited SGSN' contacts the HLR in the terminal's home network, either via the international SS7 network or by tunneling the MAP protocol messages through the Internet. The mobile terminal registers with the same home agent as before.

- 20 The ETSI group SMG12 works with UMTS architecture and evolution scenarios[umts23.30]. One idea for evolution is depicted in figure 8. The most straightforward way to implement UMTS with an already existing GPRS network is to attach the UTRAN to the Gb interface via the IWU-Gb.
- 25 However, if the UTRAN will be based on IP, a new IP based interface, Gbu, should be opened up at the SGSN, requiring an IWU-Gbu. In this description we have gone one step further and transformed the SGSN into an IWU for a core network based directly on standard IP and MobileIP.

30

UMTS, the third generation cellular system which is currently being specified by ETSI, is the first one to be optimized for extensive use of data services mixed with speech. One solution is to use the IP protocol for the transport of services across core and access networks. Using a MobileIP core network would allow roaming between UTRAN's in a rather straightforward way. However, radio resources are scarce and public cellular systems are expensive to operate, and hence, it is of great importance that the users can be properly charged for the services they are using. In the near future, it is doubtful that this requirement can be fulfilled by (Mobile)IP networks. Instead, parts from GSM/GPRS could be reused to complement the functionality of IP networks.

In this description, a network scenario is presented where the UMTS core network is based on Mobile IPv6, which supports roaming and possibly also handover between UTRAN's. Since the GSM/GPRS system already has several key functions to handle mobile users, e.g. subscriber data, access control, keys for encryption over radio, accounting information, the GPRS SGSN node should be reused to handle the setup of lower layer communication, including authentication and check of subscriber profile etc. A successful lower layer setup should be required in order to obtain a MobileIP care-of address. The mechanisms for distributing authorization and encryption keys in GSM/GPRS can also be utilized for distributing keys for the IPsec protocol.

## CLAIMS

5     1           A network (GSM/GPRS) with functionality which is  
related to distribution of keys for authorisation,  
authentication and ciphering, subscriber information handling  
and CDR generation characterised in that the functionality is  
combined with the internet protocol for transporting data and  
10 handling macro mobility to form an efficient as well as  
secure core network for mobile users.

2           A network, as claimed in claim 1, characterised in  
that parts from GSM/GPRS is reused to complement the  
15 functionality of IP networks.

3           A network, as claimed in claim 2, characterised in  
that the GPRS - SGSN is reused to handle the setup of lower  
layer communication.  
20

25

30

1/8




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4






FIGURE 5

BEST AVAILABLE COPY

6/8





FIGURE 6

BEST AVAILABLE COPY

— Data & Signalling  
..... Signaling



**BEST AVAILABLE COPY**

8/8




FIGURE 8

BEST AVAILABLE COPY

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H04L 29/06</b>	<b>A3</b>	(11) International Publication Number: <b>WO 99/56445</b> (43) International Publication Date: 4 November 1999 (04.11.99)
(21) International Application Number: PCT/SE99/00621 (22) International Filing Date: 19 April 1999 (19.04.99)  (30) Priority Data: 9801524-1 28 April 1998 (28.04.98) SE 9802666-9 4 August 1998 (04.08.98) SE  (71) Applicant (for all designated States except US): TELIA AB (publ) [SE/SE]; Mårbackagatan 11, S-123 86 Farsta (SE).  (72) Inventor; and (75) Inventor/Applicant (for US only): HUBBARD, Elisabeth [SE/SE]; Operettvägen 28, S-142 43 Skogås (SE).  (74) Agent: PRAGSTEN, Rolf; Telia Research AB, Vitsandsgatan 9, S-123 86 Farsta (SE).		(81) Designated States: EE, LT, LV, NO, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published With international search report.  (88) Date of publication of the international search report: 23 March 2000 (23.03.00)

(54) Title: A (GSM-GPRS) NETWORK WITH INTERNET PROTOCOL COMBINED FUNCTIONALITY



(57) Abstract

A network (GSM/GPRS) with functionality which is related to distribution of keys for authorisation, authentication and ciphering, subscriber information handling and CDR generation. The functionality is combined with the Internet protocol for transporting data and handling macro mobility to form an efficient as well as secure core network for mobile users.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00621

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04L 29/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04L, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9726739 A1 (NOKIA TELECOMMUNICATIONS OY), 24 July 1997 (24.07.97), abstract  --	1-3
A	WO 9715994 A1 (NOKIA MOBILE PHONES LTD.), 1 May 1997 (01.05.97), page 4, line 22 - page 6, line 26  -- -----	1-3



Further documents are listed in the continuation of Box C.



See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

20 December 1999

Date of mailing of the international search report

12 -01- 2000

Name and mailing address of the ISA/

Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Stefan Hansson/mj

Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

02/12/99

International application No.

PCT/SE 99/00621

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9726739 A1	24/07/97	AU 1445897 A	11/08/97
		EP 0875108 A	04/11/98
		FI 2482 U	19/06/96
		FI 102232 B	00/00/00
		FI 960185 A,V	16/07/97
-----			
WO 9715994 A1	01/05/97	AU 702769 B	04/03/99
		AU 6990696 A	15/05/97
		DE 19641084 A	24/04/97
		FI 955030 A	24/04/97
		FR 2740290 A	25/04/97
		GB 2306858 A,B	07/05/97
		GB 9622016 D	00/00/00
		IT 1284978 B	28/05/98
		IT MI962156 A	17/04/98
		NL 1004295 A,C	00/00/00
		SE 9603731 A	24/04/97
		US 5966378 A	12/10/99
-----			